

SYSTIMAX 360™ iPatch® 1100GS6 Evolve U/UTP Patch Panel,
24 port

Product Classification

| | |
|-----------------------|---|
| Regional Availability | Asia Australia/New Zealand EMEA Latin America North America |
| Portfolio | SYSTIMAX® |
| Product Type | RJ45 patch panel |
| Product Brand | SYSTIMAX 360™ iPatch® |

General Specifications

| | |
|-----------------------|-----------------|
| ANSI/TIA Category | 6A |
| Cable Type | Unshielded |
| Color | Silver |
| Intelligence Type | iPatch® enabled |
| Panel Style | Straight |
| Rack Units | 1 |
| Total Ports, quantity | 24 |
| Wiring | T568A T568B |

Dimensions

| | |
|--|---------------------|
| Height | 44.45 mm 1.75 in |
| Width | 482.6 mm 19 in |
| Depth | 206.5 mm 8.13 in |
| Compatible Diameter Over Dielectric, maximum | 1.168 mm 0.046 in |

Electrical Specifications

| | |
|--|-------------------------------|
| Current Rating at Temperature | 1.5 A @ 20 °C 1.5 A @ 68 °F |
| Dielectric Withstand Voltage, RMS, conductive surface | 1,500 Vac @ 60 Hz |
| Insulation Resistance, minimum | 500 MΩ |

Mechanical Specifications

| | |
|-------------------------------------|-----------|
| Plug Insertion Life, minimum | 750 times |
|-------------------------------------|-----------|

Environmental Specifications

| | |
|------------------------------|--------------------------------------|
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Storage Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |
| Safety Standard | UL cUL |

Packaging and Weights

| | |
|---------------------------|---|
| Packaging quantity | 1 |
|---------------------------|---|

Regulatory Compliance/Certifications

| Agency | Classification |
|---------------|--|
| CHINA-ROHS | Above maximum concentration value |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| ROHS | Compliant/Exempted |
| UK-ROHS | Compliant/Exempted |

